






The sizes are expressed in millimeters.

DESIGN 2001
LAMPADA DA PARETE E DA SOFFITTO - METALLO
WALL AND CEILING LAMP - METAL

SPOT

 ENDLESS SYSTEM VERSION AVAILABLE

CE IP20



1A1080300.00.04	BIANCO OPACO / MATT WHITE - PUSH	220-240 V - 50/60 Hz - MAX 21 W LED ORIENTABILE MODULO LED NON INCLUSO ACCESSORI OPZIONALI MODULO LED ADJUSTABLE LED MODULE NOT INCLUDED OPTIONAL LED MODULE ACCESSORIES
1A1080400.00.04	NERO OPACO / MATT BLACK - PUSH	

CODE	SOCKET	TENSION	WATTAGE	BEAM ANGLE (°)	TEMPERATURE (K)	SOURCE LUMENS	BULB EFFICIENCY	CRI (Ra)	DIMMABLE	PRODUCT REFERENCE	
MODULI LED DG111 / DG111 LED MODULES											
1A4700000.27.20	500 mA DC		16,7 W	15°	2700K	1648 lm	F	90	X	PUNTO PUNTO PL PUNTO 2 PL SPOT SPOT SISTEMA	
1A4700000.30.20	500 mA DC		16,7 W	15°	3000K	1682 lm	F	90	X		
1A3890000.27.20	500 mA DC		16,7 W	22°	2700K	1859 lm	F	90	X		
1A3890000.30.20	500 mA DC		16,7 W	22°	3000K	1945 lm	F	90	X		
1A3900000.27.20	500 mA DC		16,7 W	36°	2700K	1808 lm	F	90	X		
1A3900000.30.20	500 mA DC		16,7 W	36°	3000K	1890 lm	F	90	X		
1A4700000.27.20	350 mA DC		11,7 W	15°	2700K	1336 lm	F	90	X		SPOT ENDLESS SPOT ENDLESS CASAMBI
1A4700000.30.20	350 mA DC		11,7 W	15°	3000K	1364 lm	F	90	X		
1A3890000.27.20	350 mA DC		11,7 W	22°	2700K	1508 lm	F	90	X		
1A3890000.30.20	350 mA DC		11,7 W	22°	3000K	1578 lm	F	90	X		
1A3900000.27.20	350 mA DC		11,7 W	36°	2700K	1266 lm	F	90	X		
1A3900000.30.20	350 mA DC		11,7 W	36°	3000K	1323 lm	F	90	X		

ACCESSORI OPZIONALI MODULO LED / OPTIONAL LED MODULE ACCESSORIES

1A1210000.00.00	STANDARD			DARKLIGHT						PUNTO PUNTO PL PUNTO 2 PL SAMPEI 230 SAMPEI 260 SAMPEI 290 SAMPEI 440 SPOT SPOT ENDLESS SPOT ENDLESS CASAMBI SPOT SISTEMA
-----------------	----------	--	--	-----------	--	--	--	--	--	---