

Floor / wall luminaire with direct light for outdoor use.

Strength blended with elegance.

The body is in sanded matt black anodised or natural sanded aluminium and the inner frame is in sanded matt black anodised aluminium.  
The spotlight is in sanded matt black anodised aluminium and can be adjusted up to 45° in one direction. In IPE BOLLARD, a coach screw accessory is available for lawns, and a natural or matt black anodised aluminium base is available for fixing to rigid supports.

The light source is LED with integrated module.  
In IPE BOLLARD, the driver is integrated and has no dimmer function. In IPE P, the driver is not included but is available as an accessory. The electric cable is matt black and 1 m long. An electric connector is included for outdoor use.

Apparecchio di illuminazione da terra / parete, a luce diretta, per esterni.

La robustezza coniugata all'eleganza.

Il corpo è in alluminio anodizzato nero opaco sabbato o naturale sabbato e il telaio interno è in alluminio anodizzato nero opaco sabbato. Il proiettore è in alluminio anodizzato nero opaco sabbato ed è orientabile fino a 45° in una direzione. Per IPE BOLLARD è disponibile l'accessorio tirafondo per i terreni erbosi e una base in alluminio anodizzato nero opaco o naturale per fissaggio su supporti rigidi.

La sorgente luminosa è a LED e a modulo integrato.  
In IPE BOLLARD, il driver è integrato e non dimmerabile. In IPE P, il driver non è incluso, ma è disponibile come accessorio. Il cavo elettrico è di colore nero opaco e 1 m di lunghezza. È incluso un connettore elettrico per esterni.

#### Finish

**.04** Matt Black

**.44** Natural Aluminium

#### Certification

IPE BOLLARD: Luminaire US/CAN certification pending.

IPE P: Luminaire available for US/CAN market. Available for CHINA market.


IPE BOLLARD: Apparecchio illuminante con certificazione US/CAN in corso.

IPE P: Apparecchio illuminante disponibile per mercato US/CAN. Disponibile per mercato CHINA.

# IPE BOLLARD

Alberto Zattin / 2026

# IPE BOLLARD



## IPE BOLLARD

8,6W  
110-240V - 50/60Hz  
2700K - 257lm / 3000K - 257lm  
CRI >90  
Beam 25°  
UGR <19  
Driver integrated  
ON/OFF




Matt Black - 2700K - ON/OFF	1A6480400.27.00
Matt Black - 3000K - ON/OFF	1A6480400.30.00
Natural Aluminium - 2700K - ON/OFF	1A6484400.27.00
Natural Aluminium - 3000K - ON/OFF	1A6484400.30.00

## Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



<b>Base / Base</b>		Not included
Matt Black	1X0310400.01.00	
Natural Aluminium	1X0314400.01.00	




<b>Anchoring bolt / Tirafondo</b>		Not included
Cut-out Ø 250 mm Minimum space for mounting 350 mm	1X0310000.02.00	



<b>Driver connector IP68 / Connettore driver IP68</b>		Included
1 Piece	1A1660000.00.00	

The sizes are expressed in millimeters.



**IPE P**


6,4W  
24V DC  
2700K - 257lm / 3000K - 257lm  
CRI >90  
Beam 25°  
UGR <19  
Driver not included



Matt Black - 2700K	1A6500400.27.20
Matt Black - 3000K	1A6500400.30.20
Natural Aluminium - 2700K	1A6504400.27.20
Natural Aluminium - 3000K	1A6504400.30.20

**Compulsory accessories / Accessori obbligatori**

Drivers / Alimentatori



Driver / Alimentatore		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

**Optional accessories / Accessori opzionali**

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68		Not included
1 Piece		1A1660000.00.00

